

22 FT. CARGO EXTRACTION ASSEMBLY
P/N 11-1-2584
NSN 1670-01-063-3716

TECHNICAL DATA
UPDATED MAY 22, 2007

U.S. PART NO: **The standard assembly consists of:**

11-1-2584 **22 FT. CARGO EXTRACTION ASSEMBLY**

- | | | |
|----|-----------|-------------------------|
| 1. | 52K6329 | 22 Ft. Ring Slot Canopy |
| 2. | 58J6099 | Deployment Bag |
| 3. | 11-1-2582 | 60” Adapter Web |

22 FT. DIAMETER CARGO EXTRACTION PARACHUTE

All 22 Ft. Cargo Extraction Assemblies are manufactured using the latest revision of material listed in Technical Data.

All 22 Ft. Cargo Assemblies are manufactured in strict accordance with Cargo Parachute U.S. Military Specifications MIL-DTL-7620, MIL-DTL-9401, and MIL-STD-849, latest revision.

All 22 Ft. Cargo Extraction Assemblies are preserved, packaged and packed in accordance with U.S. Military Specifications or customer’s specific packaging instructions.

The 22 Ft. Extraction Canopy is of ring slot design and has 28 gores and suspension lines. When used for low-velocity airdrops, it has the capability of extracting loads ranging from 8,000 lbs. to almost 19,000 lbs., depending on the type of aircraft. The packed assembly weighs approximately 61 lbs.

In both the original configuration, P/N 59B6209, NSN 1670-00-687-5458, and this most recent configuration, P/N 11-1-2584, NSN 1670-01-063-3716, an Adapter Web is included as part of the assembly. In the original configuration a 60 Ft., 6 ply, 3-loop Extraction Line, P/N 62J4260-1, made of Type X webbing, PIA-W-27265, 1-3/4”, Camouflage Green #483, 9500# tensile strength, is also supplied as part of the assembly. The Canopy, P/N 52K6329 and Deployment Bag, P/N 58J6099, is the same for both configurations. The original configuration can be manufactured if customer requests. All 22 Ft. Diameter Cargo Extraction Parachute

Mills Manufacturing Corporation
P.O. Box 8100 Asheville, NC 28814
Telephone: 828-645-3061 Fax: 828-645-3065
Website: www.millsmanufacturing.com Email: info@millsmanufacturing.com

22 FT. CARGO EXTRACTION ASSEMBLY
PAGE 2 OF 5
TECHNICAL DATA
UPDATED 5/22/07

Assemblies' material color, Olive Drab, was revised in 1995 to the new U.S. Army material color, Camouflage Green #483.

The Deployment Bag, P/N 58J6099, was revised in 2001 to eliminate the outer and inner loop with Nylon Cord, Type VI and buffer. The new nylon reinforcement straps, PIA-W-27265, Type VIII, crossing opposite corners of the bag have been added. Pendulum line, Nylon Cord, PIA-C-7515, Type IV, is now looped around center of new reinforcement straps.

The 22 Ft. Extraction Parachute may also be used for high velocity airdrops. When used for this purpose, it will support a payload of from 501 lbs. to 2200 lbs.

Mills Manufacturing Corporation

P.O. Box 8100 Asheville, NC 28814

Telephone: 828-645-3061 Fax: 828-645-3065

Website: www.millsmanufacturing.com Email: info@millsmanufacturing.com

1. **22 Ft. Canopy, P/N 52K6329:**

Shape:	Ring Slot
Diameter:	22 Ft.
Number of Gores	28
Number of Rings Per Gore	7
Number of Suspension Lines	28
Number of Suspension Lines	22'
Ring Panel Material:	Nylon Cloth, PIA-C-7350, Type II, Camouflage Green #483, 3.5 oz., 135# tensile strength warp and fill, 150-200 CFM air permeability
Suspension Line and Vent Line Material:	Nylon Cord, PIA-C-7515, Type V, Camouflage Green #483, 1500# tensile strength
Skirt Reinforcements:	Nylon Webbing, PIA-W-5625, 1", Camouflage Green #483/Natural, 4000# tensile strength
Vent Reinforcement:	Nylon Webbing, PIA-W-4088, 1", Type XVIII, Class 2, Camouflage Green #483, 600# tensile strength, Condition U
Ring Reinforcements:	Nylon Tape, PIA-T-5038, 1/2", Type III, Class 2, Camouflage Green #483/Natural, 250# tensile strength
Radial Tapes; Pocket Bands; Radial Tape Attachment Loops:	Nylon Tape, PIA-T-5038, 1", Type IV, Camouflage Green #483, Class 2, 1000# tensile strength
Bridle Loop:	Nylon Webbing, PIA-W-27265, Type VIII, 1-23/32", Class 2, Camouflage Green #483, 4000# tensile strength

Mills Manufacturing Corporation

P.O. Box 8100 Asheville, NC 28814

Telephone: 828-645-3061 Fax: 828-645-3065

Website: www.millsmanufacturing.com Email: info@millsmanufacturing.com

Suspension Line Links: PS 70118-1, 3000# proof load

Canopy Stitching: Nylon Thread, V-T-295, Type I/II, Class A, Size E,
FF, 3-C, Natural

2. Deployment Bag, P/N 58J6099:

Type Bag: Locking Closure

Bag Material: Nylon Cloth, PIA-C-7219, Type III, Class 3,
Camouflage Green #483, 325# warp tensile strength,
275# fill tensile strength

Reinforcing Straps: Nylon Webbing, PIA-W-27265, Type VIII, 1-23/32",
Class 2, Camouflage Green #483, 4000# tensile strength

Tie Down; Tie Loops; Stow
Loops; Closure Bands: Nylon Tape, PIA-T-5038, Type IV, 1", Class 2,
Camouflage Green #483, 1000# tensile strength

Stiffener Webbing: Nylon Webbing, PIA-W-27265, Type IV, 3" Class 2,
Camouflage Green #483, 1800# tensile strength

Handle and
Pendulum Line: Nylon Cord, PIA-C-7515, Camouflage Green #483,
Type IV, 1000# tensile strength

Log Record Pocket: P/N 11-1-2587, Camouflage Green #483 material

Binding Material: Nylon Tape, PIA-T-5038, Type III, Class 2, 3/4",
Camouflage Green #483, 400# tensile strength

"V" Ring: PS 22045-1, 2500# proof load

Bent "V" Ring: PS 70115, carbon steel

Stitching: Nylon Thread, V-T-295, Type II, Class A, Size E,
3-C, Camouflage Green #483

Mills Manufacturing Corporation

P.O. Box 8100 Asheville, NC 28814

Telephone: 828-645-3061 Fax: 828-645-3065

Website: www.millsmanufacturing.com Email: info@millsmanufacturing.com

3. 60" Adapter Web, P/N 11-1-2582:

Web Material:	Nylon Webbing, PIA-W-27265, Type XXVI, Class 2, 1-23/32", Camouflage Green #483, 15000# tensile strength
Keeper Retainer and Buffer Material:	Nylon Webbing, PIA-W-27265, Type VIII, Class 2, 1-23/32", Camouflage Green #483, 4000# tensile strength
Sliding Keeper and Loop Buffer Material:	Nylon Webbing, PIA-W-27265, Type VII, Class 2, 1-23/32", Camouflage Green #483/Natural, 6000# tensile strength

3. 60" Adapter Web, P/N 11-1-2582 (continued):

Stitching:	Nylon Thread, V-T-295, Type I/II, Class A, Camouflage Green #483, Size E, 5-C
Stitching:	Nylon Thread, V-T-295, Type I/II, Class A, Camouflage Green #483/Natural, Size E, 3-C, 5-C
Handstitching:	Cotton Thread, A-A-52094, Type V, Size 8/7, Camouflage Green #483/Natural

Mills Manufacturing Corporation

P.O. Box 8100 Asheville, NC 28814

Telephone: 828-645-3061 Fax: 828-645-3065

Website: www.millsmanufacturing.com Email: info@millsmanufacturing.com